



TECHNICAL DATA SHEET

UV SIZING PRIMER

UGS-9728

DESCRIPTION

UV sizing primer is a 100% reactive UV high gloss coating and overprint for non-porous. UV Sizing Primer is also stampable, writable, and glueable. It is formulated for adhesion to ABS, acrylic, anodized aluminum, butyrate, cardboard, coated metals, coated and uncoated papers, corrugated board, polycarbonate, polyester, polystyrene, and vinyl.

FEATURES

- Writeable/Stampable/Glueable
- High Gloss
- Fast Cure
- Excellent Rub Resistance
- Excellent Adhesion
- Multi-Purpose
- Versatile

TECHNICAL SPECIFICATIONS

- **Flash Point (°F TCC):** > 200
- **VOC:** 0
- **Specific Gravity:** 1.07 g/cm³
- **Color:** Colorless
- **Solids:** 100%
- **Gluing, Stamping:** Test first due to variety of glues and foils
- **Viscosity:** 130-160 CPS @ 60 RPM and 77°F/23°C
- **Cure Speed:** 800+ FPM
- **Rub Resistance:** > 100 Rubs/5#
- **Flammability:** No
- **Gloss:** High Gloss
- **TB Test:** No Mar
- **Shelf Life:** 6 months

STORAGE

Store tightly covered at temperatures between 65-90°F. Coating taken from the press should not be returned to the original container. Store separately to avoid contamination.

DISCLAIMER: Unless otherwise restricted by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. See the Safety Data Sheets (SDS) for this product for safety information prior to use. Rev. 04/29/2016